

## Digital Pressure Gauge CPG2400 Series

mensor

### Applications

- Desk top monitoring of barometric pressure changes
- Production and test environments
- Pressure test benches

### Features

- Ranges to 6015 psi
- 0.03% FS accuracy
- Absolute, gauge, bidirectional or vacuum
- RS-232 or RS-485 communications
- 17 selectable pressure units and 1 user defined unit



Digital Pressure Gauge Model CPG2400

## Description

### General

Mensor's CPG2400 Digital Pressure Gauge is a low cost, single range pressure measuring instrument. With an accuracy of 0.03% FS and a small package design, this unit is perfect as a desktop pressure monitor or a barometer. The unique design of the CPG2400 provides peak and null features, selectable from the main menu screen. Pressure units are selectable from a choice of 17 different units and one user defined unit. The small package, combined with lower uncertainty levels, make this a perfect choice where high levels of uncertainty are not required and cost is a concern.

### Applications

The CPG2400 is ideal for use as a desktop pressure monitor, barometer, or in production and test environments as a replacement for test gauges. The CPG2400 is temperature compensated from 15 to 45 degrees Celsius and can be used in this range without degradation of accuracy. Pressure ranges are available in either absolute, gauge or bidirectional modes from as

low as 10 in.H<sub>2</sub>O to as high as 6015 psi. The price and accuracy of the DPG 2400 makes it an ideal replacement for a mercury manometer in environments where mercury may be a hazard. It is used in the health care industry, weather monitoring (as a barometer), and as a process or laboratory pressure indicator.

### Functional Flexibility

The CPG2400 has a clear LCD display with an intuitive menu structure for easy navigation within the setup screens. A membrane key pad provides the user the capability to navigate within these menus to set display features such as peak, null, pressure units. It also allows access to a password protected calibration section for recalibration of the internal sensor. The CPG2400 can be operated from a remote computer via a RS-232 or RS-485 serial port connection. The serial port can be used to configure, read or calibrate the sensor. This is useful when remote indication of the pressure is required. RS-232 is used for communication over short distances and the RS-485 for longer distances and multidrop applications.

## Specifications

<b>Pressure types</b>		Absolute, gauge, bidirectional, vacuum
<b>Pressure ranges</b>		Gauge: 0.36 to 6000 psig Absolute: 7.5 to 6015 psia Bidirectional: -0.36 to 0.36 min. psig Vacuum: -atm to 6000 max.
<b>Accuracy<sup>(1)</sup></b>		0.03% FS over compensated temperature range for 180 days.
<b>Resolution</b>		5 digits
<b>Compensated temperature</b>	°C	15 to 45
<b>Storage temperature</b>	°C	-20 to 70
<b>Pressure units</b>		psi, inHg @0°C, inHg @60°F, inH <sub>2</sub> O @4°C, inH <sub>2</sub> O @20°C, bar, mbar, mmHg @0°C, cmHg @0°C, Pa, hPa, kPa, MPa, kg/cm <sup>2</sup> , cmH <sub>2</sub> O @4°C, cmH <sub>2</sub> O @20°C, MSW @0°C
<b>Pressure interfaces</b>		7/16 - 20 SAE, Ref: 10-24, 1/8 and 1/4" FNPT adapters included
<b>Media compatibility</b>		Pressure port: Clean, dry, non-corrosive, non-combustible, non-oxidizing gases for all rated ranges. Ranges ≥ 7.5 psi: All other media compatible with aluminum, 316 stainless steel, brass, Buna N, Viton, sealant, silicone grease and RTV. Not designed for oxygen service. Cannot guarantee accuracy on media other than gases. Reference port: Clean, dry, non-corrosive gases.
<b>Warm-up time</b>	min	<1 minute
<b>Communications</b>		RS-232 or RS-485 (100 ft cable length recommended)
<b>Baud rate</b>	baud	9600 baud, N,8,1
<b>Reading rate</b>	sec	~4.6
<b>Response time</b>	mS	<252
<b>Orientation</b>		Negligible >30 psi zero offset resettable w/zero – can be completely removed with re-zeroing
<b>Power input</b>		12 VDC, .125 A
<b>Display</b>		Monochrome 128x64 LCD, with white LED backlight
<b>Weight</b>	lbs.	<1.5
<b>Case size</b>	in.	2.6" H x 4.2" W x 4.9" D
<b>Warranty</b>		One year
<b>CE</b>		Compliant to EN50081, EN50082.
<b>Options</b>		Relief valves for ranges >100 psi mounted externally. Rack mount kit.